

TOP FRAME is the new power and data supply solution for conference facilities. With its completely recessable cover, power and data can be conveniently accessed from any seat around the table. The balanced geometry of TOP FRAME fits elegantly into the tabletop and allows it to be fitted with high-quality veneers.

TOP FRAME is also elegantly simple to open: just press lightly with a finger and it opens and closes again - silently.

With its surround frame, TOP FRAME is also suitable for retrofitting. The power strips can of course be interchanged in a flash and can be equipped with Bachmann's flexible custom modules.

TOP FRAME is available in various versions: in EV1 anodised aluminium or powder-coated in RAL 9006. Other surface finishes are available on request. A veneer of up to 0.6 mm can also be glued to the flap without the dimensions of the cut-out having to be changed.

The power strip clips into the frame without tools. There is a short version with 4 modules and a long version with 8 modules to suit both TOP FRAME solutions.

**The advantages
at a glance**

- Access to power supply and data from any seat
- Silent opening
- Integrated into the top of the desk or table
- Can be installed flush with the top of the desk or table
- Version with surround frame suitable for retrofitting
- Suitable for veneer finishing
- Configuration can be freely selected
- Complete power strip can be quickly interchanged



TOP FRAME opens silently and can also be conveniently operated from the seat opposite.



TOP FRAME

Perfect elegance



Witteveen Projectinrichting
Ouderkerk a/d Amstel
Tel: 020 - 496 5030
info@witteveen.nl
www.project-inrichting.nl
www.ergonomics.nl

TOP FRAME frameless

- Includes fixing accessories

Art. no. | Version

TOP FRAME base		Black
----------------	--	-------

Top Frame base without flap, black powder-coated housing	
--	--

925.100	· 4-way · Dimensions (L x W x H): approx. 300 x 92 x 98 mm
---------	---

925.101	· 8-way · Dimensions (L x W x H): approx. 482.5 x 92 x 98 mm
---------	---

TOP FRAME cover		blasted and EV1 anodised
-----------------	--	--------------------------

Top Frame blasted and anodised cover, with fixing screws	
--	--

925.0044	· 4-way · for mounting on TOP FRAME base (art. no. 925.100)
----------	--

925.0034	· 8-way · for mounting on TOP FRAME base (art. no. 925.101)
----------	--

TOP FRAME cover		blasted and black anodised
-----------------	--	----------------------------

Top Frame blasted and black anodised cover, with fixing screws	
--	--

925.0047	· 4-way · for mounting on TOP FRAME base (art. no. 925.100)
----------	--

925.0049	· 8-way · for mounting on TOP FRAME base (art. no. 925.101)
----------	--

TOP FRAME cover		EV1 anodised
-----------------	--	--------------

Top Frame EV1 anodised cover, with fixing screws	
--	--

925.0022	· 4-way · for mounting on TOP FRAME base (art. no. 925.100)
----------	--

925.0023	· 8-way · for mounting on TOP FRAME base (art. no. 925.101)
----------	--



TOP FRAME with frame

- Includes fixing accessories

Art. no. | Version

TOP FRAME		RAL 9006
Asymmetrical surround frame, short - for 4-way power strip		
925.500	<ul style="list-style-type: none"> · Aluminium flap RAL 9006, black powder-coated housing · Dimensions (L x W x H): approx. 340.5 x 162 x 98.35 mm 	



TOP FRAME		RAL 9006
Asymmetrical surround frame, long - for 8-way power strip		
925.501	<ul style="list-style-type: none"> · Aluminium flap RAL 9006, black powder-coated housing · Dimensions (L x W x H): approx. 583 x 162 x 110 mm 	



TOP FRAME		RAL 9006
Symmetrical surround frame, short - for 4-way power strip		
925.800	<ul style="list-style-type: none"> · Aluminium flap RAL 9006, black powder-coated housing · Dimensions (L x W x H): approx. 400.5 x 192 x 98.35 mm 	



TOP FRAME		RAL 9006
Symmetrical surround frame, long - for 8-way power strip		
925.801	<ul style="list-style-type: none"> · Aluminium flap RAL 9006, black powder-coated housing · Dimensions (L x W x H): approx. 583 x 192 x 98.35 mm 	



You will find power strips suitable for Slide, Conference and Top Frame on the next two pages

4-way power strips for Slide / Conference / Top Frame

Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no. | Version



CUSTOM	4-way: 3 x custom modules + power socket outlet	Length: approx. 260 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket		
	909.002	· 1 socket outlet with earthing contact, child-proof, black, set at 35°
	909.025	· 1 French / UTE socket outlet, child-proof, black, set at 35°
	909.028*	· 1 Swiss / CH socket outlet, black, set at 0°
	909.065*	· 1 Italian / earth contact combination, black, set at 35°



CUSTOM	4-way: 2 x custom modules + power socket outlets	Length: approx. 260 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket		
	909.003	· 2 socket outlets with earthing contact, child-proof, black, set at 35°
	909.010	· 2 French / UTE socket outlets, child-proof, black, set at 35°
	909.017	· 2 Swiss / CH socket outlets, black, set at 0°
	909.029*	· 2 Italian / earth contact combination, black, set at 35°



CUSTOM	4-way: 1 x custom module + power socket outlets	Length: approx. 260 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket		
	909.004	· 3 socket outlets with earthing contact, child-proof, black, set at 35°
	909.011	· 3 French / UTE socket outlets, child-proof, black, set at 35°
	909.018	· 4 Swiss / CH socket outlets, black, set at 0°
	909.058*	· 3 Italian / earth contact combination, black, set at 35°
	909.0023*	· 2 UK 3.15 A individually fused, child-proof, black, set at 45°



CUSTOM	4-way: 4 x custom modules	Length: approx. 260 mm
Anodised aluminium profile; without power connection		
	909.000	· without socket outlets



USB CHARGER	CUSTOM	4-way: 1 x USB double charger (5.2 V / 2.15 A) + custom modules + power socket outlets	L: approx. 260 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
		909.0056	· 2 socket outlets with earthing contact, child-proof, black, set at 35° · 1 x USB double charger, 1 x custom module
		909.0059	· 2 French / UTE socket outlets, child-proof, black, set at 35° · 1 x USB double charger, 1 x custom module



8-way power strips for Conference / Top Frame

Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no. | Version


























USB CHARGER	CUSTOM	8-way: 1 x USB double charger (5.2 V / 2.15 A) + custom modules + power socket outlets	L: approx. 444 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
		909.0057	· 3 socket outlets with earthing contact, child-proof, black, set at 35° · 1 x USB double charger, 4 x custom modules
		909.0060	· 3 French / UTE socket outlets, child-proof, black, set at 35° · 1 x USB double charger, 4 x custom modules
		909.0058	· 3 UK 3.15 A individually fused, child-proof, black, set at 45° · 1 x USB double charger, 2 x custom modules


* No storage type

8-way power strips for Conference / Top Frame

Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no.	Version		
8-way: 6 x custom modules + power socket outlet		Length: approx. 444 mm	CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
909.005	· 2 socket outlets with earthing contact, child-proof, black, set at 35°		
909.012	· 2 French / UTE socket outlets, child-proof, black, set at 35°		
909.033*	· 2 Swiss / CH socket outlets, black, set at 0°		
8-way: 5 x custom modules + power socket outlet		Length: approx. 444 mm	CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
909.006	· 3 socket outlets with earthing contact, child-proof, black, set at 35°		
909.013	· 3 French / UTE socket outlets, child-proof, black, set at 35°		
909.0029*	· 2 UK 3.15 A individually fused, child-proof, black, set at 45°		
8-way: 4 x custom modules + power socket outlet		Length: approx. 444 mm	CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
909.007	· 4 socket outlets with earthing contact, child-proof, black, set at 35°		
909.014	· 4 French / UTE socket outlets, child-proof, black, set at 35°		
909.019*	· 5 Swiss / CH socket outlets, black, set at 0°		
909.050*	· 4 Italian / earth contact combination, black, set at 35°		
909.0028	· 2 UK 3.15 A individually fused, child-proof, black, set at 45°		
8-way: 3 x custom modules + power socket outlet		Length: approx. 444 mm	CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
909.008	· 5 socket outlets with earthing contact, child-proof, black, set at 35°		
909.015	· 5 French / UTE socket outlets, child-proof, black, set at 35°		
909.020*	· 6 Swiss / CH socket outlets, black, set at 0°		
909.0027*	· 3 UK 3.15 A individually fused, child-proof, black, set at 45°		
8-way: 2 x custom modules + power socket outlet		Length: approx. 444 mm	CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
909.009	· 6 socket outlets with earthing contact, child-proof, black, set at 35°		
909.016	· 6 French / UTE socket outlets, child-proof, black, set at 35°		
909.0026	· 4 UK 3.15 A individually fused, child-proof, black, set at 45°		
8-way: 8 x custom modules		Length: approx. 444 mm	CUSTOM
Anodised aluminium profile; without power connection			
909.001	· without socket outlets		

CONFERENCE guide rail set

Art. no.	Version		
CONFERENCE guide rail set		Black	
For power strips (pages 6 - 7)			
940.099	· Guide rail, plastic, black · Incl. 2 countersunk head screws 2.9 x 13 mm with Torx to DIN 7982		